

Buddyfit 19" :0 ver view

Description

- 19" LCD screen
- Surface Acoustic Wave (SAW) touch screen
- Stylish housing with a stainless steel bezel, a black metal back cabinet and an optional black metal stand

Features

- Ultra slim
- Highly durable with NEMA3/IP 55 dust and water proof Display front
- Slim hard drive bay design for easy service
- Multiple ports for maximum connectivity
- 100mm VESA standard versatile installation



Certificates



LVD

Buddyfit 19" : Specification

Display: 19" LCD TFT screen

Touch screen technology: Surface

Acoustic Wave (SAW)

Motherboard: B78

Processor: Intel Celeron M 1.5 GHz

(upgrades available)

Chipset: Intel 852GM and ICH4 FSB

400MHz

System Memory: 1GB RAM, 2 x DDR SODIMM

slot, up to 2GB

Graphic Memory: Share system memory 8 – 64MB

BIOS: AWARD BIOS

Brightness: 300NITS

Maximal Resolution: 1280 x 1024

HDD: 2.5" Slim 80 GB HDD bay

Flash Memory: Optional Compact Flash memory

(without HDD)

Mini-PCI: 1

External I / O Ports

USB: 2.04 x USB Type A

Serial / Com: RJ-45 (COM1 standard

RS-232; COM2 RS-232/422/485 selectable by

jumper; COM3 & COM4 pin with 5V or 12V

power by jumper)

Parallel: 1 x DB 25F

LAN (10/100): 1 X RJ-45 Wi-Fi module with

External antenna

Cash Drawer: 1 x RJ-11 (12V or 24V)

DC Jack: 1 x Latch type

Audio Jack: 1 x Line-out, 1 x Line-in

2nd VGA: 1 X DB 15F

Internal Interface

USB 2.0: 2

Audio

Speaker: 2 x 3W speakers

Power Adapter: DC 19V / 90W

Environment

EMC & Safety: FCC Class A, CE, LVD

Operating Temperature: 0°C – 40°C (32°F - 104°F)

Storage Temperature: -20°C - 60°C (-4°F - 140°F)

Operating Humidity: 5% - 95% RH no condensing

Storage Humidity: 5% - 95% RH no condensing

Dust & Water Proof: NEMA 3 / IP 55

Dimensions: (W x H x D) [mm] 449.2 x 374.2 x 60

17.69" x 14.73" x 2.36"

Weight: 9 kgs / 19.8 lbs

Mounting: 100mm x 100mm Standard

VESA, comes with wall bracket

OS Support: Windows XP, WEPOS, XP

Embedded, XP Professional for Embedded,

WIN 2000 Professional Embedded, Linux

Warranty: 1year RTB